



TANDEM & TRIPLE AXLE **GOOSENECK & PINTLE HYDRAULIC DOVETAIL SERIES**

Standard Features

- * Main Frame & Neck - 12" W Beam
 - 30' & Up - 19# Beam
 - 34' & Up We Recommend 22# Beam
- * Axle Options:
 - 7,000 lb. (Easy Lube)
 - 10,000 lb. & 12,000 lb. (Oil Bath)
- * Electric Brakes
- * 3" Channel Cross Members
- * 2 5/16" Adjustable Gooseneck Coupler
- * Stake Pockets
- * (2) 12,000 lb. Drop Leg Jack W/ Spring Return
- * 9' Hydraulic Dovetail
- * Power Up - Down
- * Pierced Beam (10K & 12K)
- * 30' to 40' Standard
- * Rub Rail
- * 2" x 8" Douglas Fir Floor
- * L.E.D. Rubber Mounted Lights
- * Modular Wiring Harness
- * Tire & Wheel Options:
 - 7K: ST235/80R16 10 ply Tires (Load Range E) on 16x6jj 8 Bolt Wheels
 - 10K & 12K: ST235/80R16 10 ply Tires (Load Range E) on 16x6k 8 Bolt Wheel
- * Primed & Painted



ABU Trailers Inc.
606 Miller St. Dwight, ND 58075
Phone: 701-642-9771
Fax: 701-642-9811
www.abustrailers.com

GOOSENECK & PINTLE HYDRAULIC DOVETAIL SERIES cont.

Optional Features

- * Axle Upgrades:
 - 7K to 8K
 - 10K to 10K Heavy Duty
 - Torsion
- * Beam Upgrades:
 - 14# to 19#
 - 19# to 22#
- * Coupler Options:
 - King Pin
 - Pintle
- * D-Rings
- * Floor Options
 - Steel or Treated
- * Jack Options
 - 2-Speed or Hydraulic
- * Neck Options
 - Deck Over The Neck (6'x8') or Mesh In The Neck
- * No Rubrail
- * Paint Underside
- * Spare Tire Bracket
- * Spare Tire & Wheel
- * Trailer Storage
 - Chainbox w/ Lid or Toolbox



Various Hydraulic Dovetail Views



Various Hydraulic Dovetail Views



Various Hydraulic Dovetail Views



Various Hydraulic Dovetail Views



Toolbox in Neck—Above Chainbox With Lid—Below



Spare Tire Bracket In Neck



Rear View Hyd. Dovetail



Hydraulic Dovetail