

Tandem Axle 7,000 Series

Standard Features:

3,500 lb. Tandem Brake Axles
7,000 lb. GVW
Spring Suspension
2" A-Frame Coupler
Straight or 2' Dovetail
Wrap Around Hitch
5" Channel Frame & Hitch
Channel Cross Members
82" Wide Between Fenders
9" x 72" Removable Fenders
6' Removable Front Rail
2" x 8" Douglas Fir Floor
Stored Ramps
2,000 lb. Top Wind Swivel Jack
L.E.D. Rubber Mounted Lights
Modular Wiring Harness
ST205/75R15 6 ply Tires (Load Range C)
15x5JJ 5 Bolt Wheels
Primed & Painted

Optional Features:

7,000 lb. Drop Leg Jack
Paint Underside
Poly Tongue Mounted Toolbox
D-Rings
Drop Stands

Axle Options:

Drop or Torsion

Brake Options:

One Brake or Surge

Coupler Options:

*2" Bulldog
2" Adjustable or Gooseneck*

Fender Options:

*14 Gauge Removable Tread Plate
1/8" Heavy Duty Tread Plate*

Floor Options:

Steel or Treated

Rail Options:

Removeable Side Rails (fit inside stake pockets) or Welded Side and Front Rail

Ramp/Gate Options:

No Ramps, Fold-Ups or Light